



**MSRP: \$4099**

**Color: Blue Steel**

## SPECIFICATIONS

Suggested Use	Gravel, Road, Adventure
Sizes	Small, Medium, Large
Total Weight	L: 46.7 M: 46.4, S: 46.2 (lbs.)
Frame	Yamaha Hydroformed Aluminum. Integrated battery. Water bottle boss. Internal shift/brake hose routing
Fork	One-Piece Aluminum. 12x100mm Thru-Axle. Fender and rack compatible. Internal brake hose routing
Battery	Yamaha Lithium Ion 500Wh, 36V, 13.4Ah
Drive Unit	Yamaha PWSeries ST 3-bolt Mount, Display A
Crankarm	Square Taper Spindle Length S-165mm, M and L - 170mm
Chainring	Shimano GRX 44t
Shifter	Shimano GRX 11-speed RX600
Rear Derailleur	Shimano GRX RX812
Brakes	Shimano GRX RX400 front/rear
Rotors	Shimano SM RT64, 180mm front, 160mm rear
Cassette	Shimano CS-M7000 11-42t 11-Speed
Chain	KMC e11 Turbo EPT 120 links
Hubs	Front: 12x100mm Quick-Release Thru-Axle (QRTA) Rear: 12x142mm QRTA with integrated speed sensor
Rims	32-Hole, Dual Channel Welded Pin w/ Eyeleted Spoke External Rim Width=25mm Internal Rim Width=22mm
Spokes	SUS304 14G w/ brass nipple
Tires/Tubes	Maxxis Rambler 700 x 45c TR EXO 120tpi
Headset	Integrated bearing with 30mm of spacers
Stem	31.8 clamp dia. 6 deg rise S-80mm, M-90mm, L-100mm
Handlebar	Flare Drop. 31.8 dia. 46cm c-c "width at hood", 58cm c-c "width at drop"
Grips/Tape	Padded Cork Tape
Seatpost	30.9 diam. Limotec Suspension Dropper Post Total Post Length: (M,L) 345mm (S) 295mm Dropper Travel, (M,L) 60mm (S) 40mm Suspension Travel (S,M,L) 40mm
Seatpost Collar	Alloy 2-bolt 35.0mm diameter 2-bolt
Saddle	Yamaha Off-Road Cro-Mo Rail

## FEATURES

- Ergonomics and geometry designed for gravel riding
- Tubeless conversion ready wheels and tires for off-road
- Gravel handlebar with wide-flare
- Adjustable dropper post with 40mm suspension travel
- Fender and front/rear rack compatible
- Quad Sensor System with rear hub speed sensor
- Rated power: 250W (Nominal), 500W (Max.)
- Max. torque: 70Nm
- Max. speed support: 28mph
- 5 Assist modes: AUTO, ECO+, ECO, STANDARD, HIGH
- Walk Assist Feature
- Accessories** Yamaha keys  
Yamaha battery charger  
Bell
- Warranty** 3-Year on Frame, Drive Unit, Battery\*

## FRAME GEOMETRY

	SMALL	MEDIUM	LARGE
TOP TUBE (effective)	535	565	595
REACH LENGTH	368	382	402
STACK HEIGHT	595	607	617
STANDOVER HEIGHT	781	818	852
HEADTUBE LENGTH	121	131	142
HEADTUBE ANGLE	71.1	71.8	71.9
SEAT TUBE ANGLE	74.4	73.3	72.6
SEAT TUBE LENGTH	429	490	551
SEAT POST LENGTH	340	395	440
DROPPER POST TRAVEL	75	100	125
STEM LENGTH	70	70	70
BB DROP	73	73	73
WHEELBASE	1057	1068	1090
REAR CENTER	464	464	464
CRANKARM LENGTH	172.5	172.5	172.5
HANDLEBAR WIDTH	44	44	44

\*Full Details on Warranty Sheet