





SPECIFICATIONS

Saddle

Suggested Use	All-Mountain Trail		
Size	Small, Medium, Large		
Total Weight	53.4lbs		
Frame	YAMAHA Dual Twin		
Fork	RockShox Revelation RC 160mm Boost		
Rear Shock	RockShox Deluxe Select + 210x55 160mm travel		
Battery	YAMAHA Multilocation 500Wh 36V Lithium Ion		
Drive Unit	YAMAHA exclusive PW-X2 Quad Sensor System with new AUTO, MTB and Push Assist modes		
Crankarm	ISIS Spline. 170mm		
Chainring	36t 104BCD		
Shifter	Shimano SLX		
Rear Derailleur	Shimano SLX		
Brakes/Rotors	Magura MT30 with 203mm Storm CL rotors. Front 4-Piston, Rear 2-Piston		
Cassette	Shimano SLX 11s 11-46t		
Chain	KMC e11 Turbo		
Wheelset	YAMAHA 27.5+ Alloy. Tubeless tape installed. 40mm inner rim width		
Tires	Front CST BFT 2.8" Rear CST Patrol 2.8"		
Headset	Integrated tapered with 30mm steerer spacers		
Stem	YAMAHA Alloy 4-bolt faceplate, 35.0 dia., 40mm length.		
Handlebar	YAMAHA Alloy 30mm rise, 35.0 dia., 780mm wide		
Grips	Locking Dual Core		
Seatpost	Alloy 30.9 dia. dropper post. (S/M) 125mm travel, (L) 150mm travel.		
Seatpost Collar	Single-bolt. 35.0mm dia.		
-			

YAMAHA Anti-Slip with Hand Rail Tail

FEATURES

Dual Twin frame design

160mm All Mountain Travel Front and Rear

27.5+ Tubeless Ready Wheelset

All-New PW-X2 with Quad Sensor System

Rear hub speed sensor

Max torque: 80 Nm

Max cadence support: 170rpm

5 Manual Assist Modes: ECO, STANDARD, HIGH, MTB, EXPW

Automatic Mode: ECO, STANDARD HIGH

Internal cable/housing routing

3-Year Warranty* on Frame, Drive Unit, Battery

Component manufacturer's warranty is supported by YAMAHA
* Full details on warranty sheet

FRAME GEOMETRY

 	<u> </u>	7 \ 7	
	Small	Medium	Large
Top Tube	572	619	666
Reach	388	432	478
Stack	611	619	624
Standover Height	746	755	763
Head Tube Length	111	120	125
Head Tube Angle	66.3	66.3	66.3
Seat Tube Length	390	400	410
Seat Tube Angle	70.3	70.3	70.3
BB Drop	19	19	19
Wheelbase	1157	1205	1253
Rear Center	469	469	469